

Broadband Standard Product
PA001040-32 GaN High Efficiency Driver Amplifier
Broadband Power 100MHz to 4GHz

February 9, 2009

www.aeroflex.com/bband



DESCRIPTION

The PA001040-32 is a broadband high efficiency driver amplifier in a compact package and is ideal for use as a stable gain block, IF Amplifier or Driver Power Amplifier for commercial, military or space applications.

Our team of engineers can custom design power amplifiers using the latest simulation software and proprietary technology to meet even the most demanding specifications.

FEATURES

- 0.1 to 4GHz Frequency Range
- $P_{SAT} > 32\text{dBm}$
- 10dB typical gain
- Operates from a Single +28V Supply
- Unconditionally Stable
- Compact Size
- Hermetic Package

SPECIFICATIONS

ABSOLUTE MAXIMUM RATINGS¹

PARAMETER	SYMBOL	MIN	MAX	UNITS
Operating Temperature – Case	T_{MO}	-55	+95	°C
Storage Temperature – Case	T_{MS}	-65	+125	°C
Positive Supply Voltage	V_{PS}	-	+32	V

1. Stresses above those listed under "Absolute Maximums Rating" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

NOMINAL OPERATING CONDITIONS

PARAMETER	CONDITIONS	MIN	MAX	UNITS
Temperature, T_C – Case	Full Range	-55	+85	°C
Positive Supply Voltage, V_{PS}		+27.75	+28.5	V


Aeroflex Plainview

SPECIFICATIONS


ELECTRICAL CHARACTERISTICS @ +25°C

PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
Frequency Range		0.1	-	4	GHz
Power Output	PSAT	-	+32	-	dBm
Power Output Variation	Over Frequency	-1	-	+1	dBm
Gain		-	10	-	dB
RF Input Impedance	Reference to 50 ohms	-	2.0:1	-	-
RF Output Impedance	Reference to 50 ohms	-	2.5:1	-	-
OIP3		-	40	-	dBm
Positive Supply Voltage		-	+28	-	V
Quiescent Positive Supply Current		-	115	-	mA
Efficiency		-	35	-	%


TYPICAL INPUT RETURN LOSS




TYPICAL OUTPUT RETURN LOSS



TYPICAL GAIN



OUTLINE DRAWING



PIN	FUNCTION	PIN	FUNCTION
1	RFIN	4	+28V
2	NC	5	NC
3	RFOUT	6	GND

ORDERING INFORMATION

MODEL NUMBER	HERMETICITY	PACKAGE
PA001040-32	Non-Hermetic	0.200L x 0.200W x .076Ht
PA001040-32-H	Hermetic, Class H	

PLAINVIEW, NEW YORK
Toll Free: 800-THE-1553
Fax: 516-694-6715

INTERNATIONAL
Tel: 805-778-9229
Fax: 805-778-1980

NORTHEAST
Tel: 603-888-3975
Fax: 603-888-4585

SE AND MID-ATLANTIC
Tel: 321-951-4164
Fax: 321-951-4254

WEST COAST
Tel: 949-362-2260
Fax: 949-362-2266

CENTRAL
Tel: 719-594-8017
Fax: 719-594-8468

www.aeroflex.com info-ams@aeroflex.com

Aeroflex Microelectronic Solutions reserves the right to change at any time without notice the specifications, design, function, or form of its products described herein. All parameters must be validated for each customer's application by engineering. No liability is assumed as a result of use of this product. No patent licenses are implied.



Our passion for performance is defined by three attributes represented by these three icons: solution-minded, performance-driven and customer-focused