

Errata Sheet

GPSG-1000 Operation Manual (p/o 88037)

EXPORT CONTROL WARNING: This document contains controlled technology or technical data under the jurisdiction of the Export Administration Regulations (EAR), 15 CFR 730-774. It cannot be transferred to any foreign third party without the specific prior approval of the U.S. Department of Commerce, Bureau of Industry and Security (BIS). Violations of these regulations are punishable by fine, imprisonment, or both.

NOTICE

The following items are applicable to S/W release:

1.0.0,201109081459

NOTICE

All initial production GPSG-1000's will be shipped with 12 Satellite Vehicle capability. In a near future release, customers who have purchased the 12 SV option will retain the 12SV capability; all others will revert to 6SV capability.

ERRATA STATEMENTS (Items to be addressed in the next release:

- (1) Simulation Page: Altitude Field is WGS84 ellipsoid, not MSL.
- (2) Unit may fail to boot occasionally. Restarting the unit should resume normal operation.
- (3) Due to software limitations, there is a possibility that the GPSG-1000 could fail to respond to user inputs and no longer provide a PVT solution after a minimum of 20 hours of continuous operation. The work around is to cycle power on the GPSG-1000 and restart the simulation.

ERRATA STATEMENTS (Items to be addressed in Phase II and III release.

1. Dynamic simulation is not currently supported.
2. GPS Signals L1C, L2C and Galileo signals E5b, E6 are not currently supported.
3. The Self Test function is not currently supported.